

WHAT IS CLAIMED IS:

380

1. A method of processing a band-limited, over-sampled signal comprising: reducing the amplitude of those portions of the signal having peaks above a threshold value; and controlling the frequency position of the noise associated with the reduction of such peaks.

385

2. The method of claim 1 wherein the step of reducing the amplitude comprises: clipping the signal relative to the threshold; filtering the clipped signal; and combining the filtered clipped signal with the band-limited, over-sampled signal.

390

3. The method of claim 2 wherein the step of clipping the signal comprises: limiting the amplitude of the signal to the threshold; and subtracting the limited signal from the band-limited, over-sampled signal.

395

4. The method of claim 2 wherein the step of filtering the clipped signal comprises creating a pulse having a pre-determined shape dependent upon the clipped samples.

400

5. The method of any of claims 2 to 4 wherein the step of combining comprises subtracting the filtered signal from the band-limited, over-sampled signal.

405

6. The method of claim 2 wherein the step of combining comprises delaying the band-limited, over-sampled signal by an amount corresponding to the time taken to implement the clipping and filtering steps.

410

7. The method of claim 1 wherein the step of moving the noise comprises filtering.

415

8. The method of claim 1 wherein the step of controlling the frequency position of the noise comprises moving the noise outside the frequency band used by the signal.

420 9. The method of claim 1 wherein the step of controlling the frequency position of the noise comprises moving the noise outside the frequency band used by a signal transmitted in the opposite direction.

425 10. The method of claim 9 wherein the signal contributes an echo to the signal transmitted in the opposite direction.

11. A method of processing a band-limited, over-sampled signal comprising: clipping the signal at a given threshold;
430 subtracting the clipped signal from the signal; filtering the subtracted signal to thereby control the frequency position of the clipping noise; delaying the signal; and subtracting the filtered signal from the delayed signal, thereby reducing the amplitude of those portions of the signal having peaks above
435 the threshold.

12. A circuit for processing a band-limited, over-sampled signal, comprising: circuitry for reducing the amplitude of those portions of the signal having peaks above a threshold
440 value; and circuitry for controlling the frequency position of the noise associated with the reduction of such peaks.

13. The circuit of claim 12 wherein the circuitry for reducing comprises: a limiter for clipping the signal relative
445 to the threshold; a filter for filtering the clipped signal; and an arithmetic unit for combining the filtered clipped signal with the signal.

14. The circuit of claim 13 wherein the arithmetic unit is a
450 subtractor.

15. The circuit of claim 12 further including a delay circuit for providing a delayed version of the signal to the arithmetic unit.

455

16. The circuit of claim 12 wherein the circuitry for controlling the frequency position of the noise comprises a filter.

460

17. The circuit of claim 12 wherein the circuitry for controlling the frequency position of the noise controls the noise to be positioned outside the frequency band used by the signal.

465

18. The circuit of claim 12 wherein the circuitry for controlling the frequency position of the noise controls the noise to be positioned outside the frequency band used by a signal transmitted in the opposite direction.

470

19. The circuit of claim 18 wherein the signal contributes an echo to the signal transmitted in the opposite direction.

475

20. A circuit for processing a band-limited, over-sampled signal comprising: a limiter for clipping the signal to a given threshold; a first subtractor for subtracting the clipped signal from the multi-carrier signal, thereby generating clipped samples; a filter for filtering the clipped samples to thereby control the frequency position of the clipping noise; a delay circuit for generating a delayed version of the multi-carrier signal; and a second subtractor for subtracting the filtered clipped samples from the delayed multi-carrier signal, wherein the amplitude of those portions of the signal having peaks above the threshold is reduced.

485